



pears.getword



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."getword" IS
{CREATE FUNCTION getword

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN s1 long VARCHAR,IN ln1 SMALLINT)
RETURNS CHAR(200)
BEGIN
  DECLARE i SMALLINT;
  DECLARE ln SMALLINT;
  DECLARE s CHAR(200);
  SET ln=ln1;
  SET s=s1;
loop1: loop
  SET ln=ln-1;
  IF ln <= 0 THEN
    leave loop1
  END IF;
  SET i=charindex("char"(32),s);
  IF i > 0 THEN
    SET s=stuff(s,1,i,'')
  ELSE
    SET s=''
  END IF
END loop loop1;
SET i=charindex("char"(32),s);
IF i > 0 THEN
  SET s="left"(s,i-1)
END IF;
RETURN(s)
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getword

Last update: **2026/08/07 19:24**

