



pears.GetWorkPatternWeeklyHours



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetWorkPatternWeeklyHours"
IS
{CREATE FUNCTION GetWorkPatternWeeklyHours

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN placid CHAR(20), IN pstartdate DATE, IN penddate DATE)
RETURNS DOUBLE
BEGIN
DECLARE Absense INTEGER;
DECLARE Hours DOUBLE;
DECLARE Days INTEGER;
DECLARE WeekHours DOUBLE;
SELECT
(SELECT COUNT(state) FROM TempShift WHERE shiftdate BETWEEN pStartDate AND
pEndDate AND tempshift.state IN ('H','U') AND tempshift.personid =
employment.personid) AS Absense,
Placement.WorkNormalHours AS Hours,
(isnull(Placement.WorkMonday,0) +
isnull(Placement.WorkTuesday,0) +
isnull(Placement.WorkWednesday,0) +
isnull(Placement.WorkThursday,0) +
isnull(Placement.WorkFriday,0) +
isnull(Placement.WorkSaturday,0) +
isnull(Placement.WorkSunday,0) ) - Absense AS Days,
(IF Days > 0 THEN Days * Hours ELSE 0 endif) AS WeekHours
INTO Absense, Hours, Days, WeekHours
FROM placement KEY JOIN employment WHERE placementid = placid;
RETURN isnull(weekhours,0);
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getworkpatternweeklyhours

Last update: **2026/08/07 19:24**

