



pears.GlobalDocumentSelect



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GlobalDocumentSelect" IS
{CREATE FUNCTION GlobalDocumentSelect

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN pDescription CHAR(50) DEFAULT NULL, IN pDocumentTypeID CHAR(20) DEFAULT
NULL, IN pAgencyID CHAR(20) DEFAULT NULL, IN pDivisionID CHAR(20) DEFAULT
NULL,
  IN pDepartmentID CHAR(2) DEFAULT NULL, IN pWebPublish SMALLINT DEFAULT
NULL, IN pWebUserClassID CHAR(20) DEFAULT NULL)
RETURNS CHAR(20)
BEGIN
/* Specify pDescription and/or pDocumentTypeID plus any of the other
parameters to narrow it down*/
FOR docs AS curs no scroll cursor FOR
SELECT top 1
  g.globaldocumentID,
  isnull(description,'') AS xdescrip,
  isnull((SELECT FIRST divisionid FROM globaldocumentlink WHERE
globaldocumentID = g.globaldocumentID AND divisionid = pDivisionID ORDER BY
1), '') AS xdiv,
  (SELECT COUNT(*) FROM globaldocumentlink WHERE globaldocumentID =
g.globaldocumentID AND divisionid IS NOT NULL) AS xdivcnt,
  isnull((SELECT FIRST departmentid FROM globaldocumentlink WHERE
globaldocumentID = g.globaldocumentID AND departmentid = pDepartmentID ORDER
BY 1), '') AS xdept,
  (SELECT COUNT(*) FROM globaldocumentlink WHERE globaldocumentID =
g.globaldocumentID AND departmentid IS NOT NULL) AS xdeptcnt,
  isnull(b.publishtowebs,0) AS xpublish,
  isnull(agencyid,'') AS xagency,
  isnull(documenttypeid,'') AS xdoctype,
  isnull(ixxnetuserclassid,'') AS xuserclass,
  LENGTH(string(xagency,xdiv,xdept,xdoctype,xuserclass)) AS xmatch
FROM
  globaldocument g JOIN blobstore b ON b.id=g.globaldocumentID AND
```



```
b.class='G'
WHERE
  (isnull(pDescription,xdescrip)=xdescrip)
  AND
  (isnull(pAgencyID,'')=xagency OR xagency='')
  AND
  (isnull(pDivisionID,'')=xdiv OR xdivcnt=0)
  AND
  (isnull(pDepartmentID,'')=xdept OR xdeptcnt=0)
  AND
  (isnull(pDocumentTypeID,xdoctype)=xdoctype)
  AND
  (isnull(pWebUserClassID,'')=xuserclass OR xuserclass='')
  AND
  (isnull(pWebPublish,xpublish)=xpublish)
  AND
  isnull(g.defunct,0)=0
ORDER BY xmatch DESC FOR READ ONLY do
  RETURN globaldocumentID;
END FOR;
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_globaldocumentsselect

Last update: **2026/08/07 19:24**

