



pears.iqacCreateNominal



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."iqacCreateNominal"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "pNominalCode" CHAR(12),IN "pNominalType" CHAR(1),IN "pName"  
  CHAR(50),IN "pNominalGroup" CHAR(12),IN "pLedgerRelationship" CHAR(30),IN  
  "pLedgerID" CHAR(12),IN "pAccountCode" CHAR(12),OUT "oResult" CHAR(250) )  
BEGIN  
  IF("isnull"("pNominalCode",'') = '') THEN  
    SET "oResult" = '99:~Missing input';  
    RETURN  
  END IF;  
  IF EXISTS(SELECT "NominalCode" FROM "iqacnominal" WHERE "NominalCode" =  
"pNominalCode") THEN  
    -- dont care about ledger  
    SET "oResult" = '0:~Already exists';  
    RETURN  
  END IF;  
  INSERT INTO "iqacnominal"(  
"NominalCode","NominalType","Name","NominalGroup","LedgerRelationship","LedgerID","AccountCode" ) VALUES(  
"pNominalCode","pNominalType","pName","pNominalGroup","pLedgerRelationship",  
"pLedgerID","pAccountCode" ) ;  
  IF @@rowcount = 0 THEN  
    SET "oResult" = '1:~Insert failed';  
    RETURN  
  END IF;  
  SET "oResult" = '0:~Success'  
exception  
  WHEN others THEN  
    resignal  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."iqacCreateNominal" IS  
{CREATE PROCEDURE iqacCreateNominal
```



```
/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN pNominalCode CHAR(12),IN pNominalType CHAR(1),IN pName CHAR(50),IN
pNominalGroup CHAR(12),IN pLedgerRelationship CHAR(30),IN pLedgerID
CHAR(12),IN pAccountCode CHAR(12),OUT oResult CHAR(250))
BEGIN
  IF(isnull(pNominalCode,'') = '') THEN
    SET oResult='99:~Missing input';
    RETURN
  END IF;
  IF EXISTS(SELECT NominalCode FROM iqacnominal WHERE NominalCode =
pNominalCode) THEN
    -- dont care about ledger
    SET oResult='0:~Already exists';
    RETURN
  END IF;
  INSERT INTO iqacnominal(
NominalCode,NominalType,Name,NominalGroup,LedgerRelationship,LedgerID,Account
tCode) VALUES(
pNominalCode,pNominalType,pName,pNominalGroup,pLedgerRelationship,pLedgerID,
pAccountCode) ;
  IF @@rowcount = 0 THEN
    SET oResult='1:~Insert failed';
    RETURN
  END IF;
  SET oResult='0:~Success'
exception
  WHEN others THEN
    resignal
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_iqaccreatenominal

Last update: 2026/08/07 19:24

