



pears.IQacJournalOutstandingAmount



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."IQacJournalOutstandingAmount" IS
{CREATE FUNCTION IQacJournalOutstandingAmount

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN DocID CHAR(8),IN LineNo SMALLINT)
RETURNS DECIMAL(12,2)
BEGIN
    DECLARE rv DECIMAL(12,2);
    DECLARE amt DECIMAL(12,2);
    SET amt=0.0;
    SET rv=0.0;
    // ONLY makes sense FOR suballocatable LINES
    SELECT FIRST allocamount INTO amt FROM iqacjournal WHERE documentid =
DocID AND linewidth = LineNo;
    SELECT SUM(allocatedamount) INTO rv FROM iqacallocation WHERE
allocateddocumentid = DocID AND allocatedlinewidth = LineNo;
    SET rv=isnull(amt,0.0)-isnull(rv,0.0);
    RETURN rv
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_iqacjournaloutstandingamount

Last update: 2026/08/07 19:24

