



pears.iqmoneynumeric



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."iqmoneynumeric" IS
{CREATE FUNCTION iqmoneynumeric

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN val NUMERIC)
RETURNS NUMERIC
BEGIN
DECLARE c NUMERIC;
DECLARE neg tinyint;
SET neg = 0;
IF val < 0 THEN
    SET neg = 1;
END IF;
SET c = ("truncate"(abs(val*1000) + 0.5,0) / 1000);
IF neg=1 THEN
    SET c = 0 - c;
END IF;
SET neg = 0;
IF c < 0 THEN
    SET neg = 1;
END IF;
SET c = "truncate"(abs(c*100) + 0.5,0)/100;
IF neg=1 THEN
    SET c = 0 - c;
END IF;
RETURN c
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_iqmoneynumeric

Last update: **2026/08/07 19:24**

