



pears.IQXNetDecodePostValue



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."IQXNetDecodePostValue" IS
{CREATE FUNCTION IQXNetDecodePostValue

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(
  IN pdata CHAR(250) )
RETURNS CHAR(250)
BEGIN
  DECLARE rv CHAR(250);
  DECLARE i SMALLINT;
  DECLARE l SMALLINT;
  DECLARE c SMALLINT;
  DECLARE s CHAR(3);
  SET rv = '';
  SET l = LENGTH(pdata);
  SET i = 1;
  while i <= l loop
    SET s = substr(pdata,i,1);
    SET i = i+1;
    IF s = '+' THEN
      SET s = ' ';
    ELSE IF s = '%' THEN
      SET c = hextoint(substr(pdata,i,2));
      SET i = i+2;
      IF c = 194 THEN // utf-8 2 byte code
        SET s = ' ';
      ELSE
        SET s = "char"(c)
      END IF
    END IF END IF;
    SET rv = rv+s
  END loop;
  RETURN rv
END
```



2026/08/08 02:00

2/2

pears.IQXNetDecodePostValue

}

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_iqxnetdecodepostvalue

Last update: **2026/08/07 19:24**

