



pears.IQXNetHasPermission



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."IQXNetHasPermission" IS
{CREATE FUNCTION IQXNetHasPermission

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN pWebUserID CHAR(20),IN pRightID CHAR(20))
RETURNS SMALLINT
NOT deterministic
BEGIN
    DECLARE rv SMALLINT;
    SET rv=0;
    IF(SELECT FIRST isnull((SELECT FIRST Assigned FROM IQXNetRightAssigned
WHERE IQXNetRightID = a.IQXNetRightID AND IQXNetUserID = u.IQXNetUserID),0)+
        isnull((SELECT FIRST 1 FROM IQXNetRightDefault WHERE IQXNetRightID =
a.IQXNetRightID AND IQXNetUserClassID = a.IQXNetUserClassID AND ID =
a.ID),0) FROM
        IQXNetRightAllowed AS a JOIN IQXNetUser AS u ON a.IQXNetUserClassID =
u.IQXNetUserClassID AND a.ID = '*' WHERE
        u.IQXNetUserID = pWebUserID AND a.IQXNetRightID = pRightID) > 0 THEN
        SET rv=1
    END IF;
    RETURN rv
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_iqxnethaspermission

Last update: 2026/08/07 19:24

