



pears.IQXNetRequestAction



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."IQXNetRequestAction"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "pWebUserID" CHAR(20),IN "pActionType" CHAR(50),IN "pTargetType"  
    CHAR(20),IN "pTargetID" CHAR(20) )  
BEGIN  
    INSERT INTO "IQXNetAction"(  
        "IQXNetActionID","IQXNetUserID","ActionType","TargetType","TargetID","Action  
        State","WhenRequested" ) VALUES  
        (  
            "uniquekey"("pActionType"+"pTargetType"+"pTargetID"),"pWebUserID","pActionTy  
            pe","pTargetType","pTargetID",'0',CURRENT TIMESTAMP )  
        )  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."IQXNetRequestAction" IS  
{CREATE PROCEDURE IQXNetRequestAction  
  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  
    (IN pWebUserID CHAR(20),IN pActionType CHAR(50),IN pTargetType CHAR(20),IN  
    pTargetID CHAR(20))  
    BEGIN  
        INSERT INTO IQXNetAction(  
            IQXNetActionID,IQXNetUserID,ActionType,TargetType,TargetID,ActionState,WhenR  
            equested) VALUES(  
            uniquekey(pActionType+pTargetType+pTargetID),pWebUserID,pActionType,pTargetT  
            ype,pTargetID,'0',CURRENT TIMESTAMP)  
        )  
    END  
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_iqxnetrequestaction

Last update: **2026/08/07 19:24**

