



pears.IQXNetSwitchValue



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."IQXNetSwitchValue" IS
{CREATE FUNCTION IQXNetSwitchValue

/* Application Maintained Function / Procedure - DO NOT EDIT*/

( IN pWebUserID CHAR(20),IN pIQXNetSwitchID CHAR(50) )
RETURNS CHAR(250)
NOT deterministic
BEGIN
    DECLARE irv INTEGER;
    DECLARE rv CHAR(250);
    DECLARE xIQXNetUserClassID CHAR(20);
    SELECT IQXNetUserClassID INTO xIQXNetUserClassID FROM IQXNetUser WHERE
IQXNetUserID = pWebUserID;
    SELECT
NULLIF(IQXNetOverrideSwitchValue(xIQXNetUserClassID,pWebUserID,IQXNetSwitchI
D,VALUE),0),
NULLIF(TRIM(IQXNetOverrideSwitchTextValue(xIQXNetUserClassID,pWebUserID,IQXN
etSwitchID,TextValue)),'')
    INTO irv,rv FROM IQXNetSwitch WHERE IQXNetSwitchID = pIQXNetSwitchID;
    IF irv IS NOT NULL THEN
        RETURN isnull(rv,string(irv))
    END IF
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_iqxnetswitchvalue

Last update: 2026/08/07 19:24

