



pears.MakeKeyName



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."MakeKeyName" IS
{CREATE FUNCTION MakeKeyName

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN sSource CHAR(60))
RETURNS CHAR(60)
BEGIN
  DECLARE rv CHAR(60);
  DECLARE isin CHAR(50);
  DECLARE c CHAR(1);
  SET rv='';
  SET isin='ABCDEFGHIJKLMNOPQRSTUVWXYZ&0123456789';
  SET isin=isin+CHAR(39);
  IF isnull((SELECT removespacesfromkeynames FROM params),0) = 0 THEN
    SET isin=isin+' '
  END IF;
  SET ssource=TRIM(ucase(csconvert(ssource,'ascii')));
  while LENGTH(ssource) > 0 loop
    SET c="left"(ssource,1);
    IF charindex(c,isin) > 0 THEN
      SET rv=rv+c
    END IF;
    SET ssource=stuff(ssource,1,1,'')
  END loop;
  IF TRIM(rv) = '' THEN SET rv = 'UNKNOWN' END IF;
  RETURN(rv)
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_makekeyname

Last update: **2026/08/07 19:24**

