



pears.MasterRosterTempAllowed



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."MasterRosterTempAllowed" IS
{CREATE FUNCTION MasterRosterTempAllowed

/* Application Maintained Function / Procedure - DO NOT EDIT*/

( IN ppersid CHAR(20),IN pmastershiftid CHAR(20) )
RETURNS INTEGER
BEGIN
    DECLARE ionly INTEGER;
    DECLARE iactive INTEGER;
    IF pmastershiftid IS NULL THEN
        RETURN 1
    END IF;
    IF ppersid = (SELECT defaultpersonid FROM masterrostershift WHERE
masterrostershiftid = pmastershiftid) THEN
        RETURN 1
    END IF;
    SELECT isnull(r.useonlypreferred,0),isnull(p.active,0) INTO ionly,iactive
    FROM masterrostershift AS s KEY JOIN masterroster AS r LEFT OUTER JOIN
MasterRosterPreferredPerson AS p
        ON r.MasterRosterID = p.MasterRosterID AND p.PersonID = ppersid
    WHERE s.masterrostershiftid = pmastershiftid;
    IF ionly = 0 THEN
        RETURN 1
    ELSE
        RETURN iactive
    END IF
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_masterrosterTempallowed

Last update: **2026/08/07 19:24**

