



pears.NetAPIProc



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetAPIProc"( IN "pWebUserID" CHAR(20),IN "pOwner"
CHAR(50),IN "pName" CHAR(50) )
RESULT( "ProcBody" long VARCHAR )
// IQXWeb
BEGIN
    SELECT "isnull"("p"."source","p"."proc_defn") FROM "sys"."sysprocedure" AS
    "p" JOIN "sys"."sysuser" AS "u" ON "p"."creator" = "u"."user_id"
    WHERE "p"."proc_name" = "pName" AND "u"."user_name" = "pOwner" AND
    "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 1
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetAPIProc" IS
{CREATE PROCEDURE pears."NetAPIProc"(IN pWebUserID CHAR(20), IN pOwner
CHAR(50), IN pName CHAR(50) )
RESULT(ProcBody long VARCHAR)
// IQXWeb
BEGIN
SELECT isnull(p.source,p.proc_defn) FROM sys.sysprocedure p JOIN sys.sysuser
u ON p.creator=u.user_id
    WHERE p.proc_name = pName AND u.user_name=pOwner AND
IQXNetHasPermission(pWebUserID,'APIDESIGN') = 1;
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netapiproc

Last update: 2026/08/07 19:24

