



pears.NetAudit



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetAudit"( IN "pWebUserID" CHAR(20),IN
"pActionType" CHAR(20),IN "pDescription" long VARCHAR DEFAULT NULL,IN
"pRecordID" CHAR(20) DEFAULT NULL )
RESULT( "pResult" CHAR(250) )
// IQXWeb
BEGIN
    INSERT INTO "IQXNetAuditLog"
        ( "IQXNetUserID", "ActionType", "Description", "RecordID" ) VALUES
        ( "pWebUserID", "pActionType", "pDescription", "pRecordID" ) ;
    SELECT '0:~Success'
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetAudit" IS
{CREATE PROCEDURE pears.NetAudit(IN pWebUserID CHAR(20), IN pActionType
CHAR(20), IN pDescription long VARCHAR DEFAULT NULL, pRecordID CHAR(20)
DEFAULT NULL)
RESULT(pResult CHAR(250))
// IQXWeb
BEGIN
    INSERT INTO IQXNetAuditLog
        (IQXNetUserID, ActionType, Description, RecordID)
VALUES
        (pWebUserID, pActionType, pDescription, pRecordID);
    SELECT '0:~Success'
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netaudit

Last update: 2026/08/07 19:24



