



pears.NetCandidateBankDetails



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetCandidateBankDetails"( IN "pWebUserID"
CHAR(20),IN "pPersonID" CHAR(20) DEFAULT NULL )
RESULT( "BankName" CHAR(30),"BankSortCode" CHAR(8),"BankAcName"
CHAR(50),"BankAcNo" CHAR(8),"BankRef" CHAR(20),"ni" CHAR(20),"TaxMethod"
INTEGER,"HideDetails" INTEGER )
// IQXWeb
BEGIN
  SET "pPersonID" = "NetCandidateValidPersonID"("pWebUserID","pPersonID");
  IF "IQXNetHasPermission"("pWebUserID",'CANDBANKDETAILSVIEW') = 0 THEN
    RETURN
  END IF;
  SELECT "e"."BankName",
    "e"."BankSortCode",
    "e"."BankAcName",
    "string"("replicate"('*', "length"("e"."bankacno")-2), "right"("e"."bankacno",
2)),
    "e"."BankRef",
    "ni",
    "e"."taxmethod",
    (IF "e"."TaxMethod" = 1 THEN 0 ELSE 1 endif) AS "HideDetails"
  FROM "person" KEY LEFT OUTER JOIN "Pay_Employee" AS "e"
  WHERE "person"."personid" = "pPersonID"
END /* DOC
```

2016-10-12 PC procedure to return bank details for candidate
2017-01-17 PC provide flag to hide all details other than paye, to avoid
candidates being able to edit payment agencies details.
2017-09-26 PC include tax details
2017-10-24 PC alter size of tax parameters
2018-04-24 PC add column to hide tax type tab
2018-05-06 PC IW-503 only display last two digits of bank code
2018-10-10 MHS IW-456 multi-cand fix and tests
2019-4-9 MHS strip out rogue tax code rubbish

Tests:



Valid pWebUserID without read permission

Valid pWebUserID with read permission

Flag names:

CandBankDetailsView

```
*/
/* TEST
NetTestSetup('');
insert into pay_employee
(Personid,bankname,banksortcode,BankAcName,BankAcNo,BankRef,secondaryagencyid) on existing update defaults off values
('TEST','TestBank','99-99-99','TestTest','09988776','TestRef','TEST');
insert into iqxnetright (IQXNetRightID,Description,sortorder) on existing update defaults off values ('CANDBANKDETAILSVIEW','View candidate bank details',998);
insert into iqxnetrightallowed
(ixxnetrightid,ixxnetuserclassid,id,maintainonweb) on existing update defaults off values ('CANDBANKDETAILSVIEW','CANDIDATE','*',1);
select * from NetCandidateBankDetails(null);
expect EOF;
select * from NetCandidateBankDetails(null);
expect EOF;
insert into iqxnetrightassigned (ixxnetuserid,ixxnetrightid,assigned) on existing update defaults off values
('test.candidate','candbankdetailsview',1);
select * from "NetCandidateBankDetails"("pWebUserID" = 'test.candidate');
expect
BankName=TestBank,BankSortCode=99-99-99,BankAcName=TestTest,BankAcNo=*****76,BankRef=TestRef;
delete from iqxnetrightassigned where ixxnetuserid='test.candidate' and ixxnetrightid='candbankdetailsview';
*/
GO
```

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetCandidateBankDetails" IS
{CREATE PROCEDURE pears."NetCandidateBankDetails"( IN "pWebUserID" CHAR(20),
IN pPersonID CHAR(20) DEFAULT NULL )
RESULT("BankName" CHAR(30),"BankSortCode" CHAR(8),"BankAcName"
CHAR(50),"BankAcNo" CHAR(8),"BankRef" CHAR(20), ni CHAR(20),TaxMethod
INTEGER, "HideDetails" INTEGER)
// IQXWeb
BEGIN
    SET pPersonID=NetCandidateValidPersonID(pWebUserID,pPersonID);
    IF "IQXNetHasPermission"("pWebUserID",'CANDBANKDETAILSVIEW') = 0 THEN
        RETURN;
    END IF;
    SELECT
```



```
e."BankName",
e."BankSortCode",
e."BankAcName",
string(replicate('*',LENGTH(e.bankacno)-2),RIGHT(e.bankacno,2)),
e.BankRef,
ni,
e.taxmethod,
(IF e.TaxMethod = 1 THEN 0 ELSE 1 endif) AS HideDetails
FROM
  person KEY LEFT OUTER JOIN "Pay_Employee" AS e
WHERE
  person.personid=pPersonID
END

/* DOC

2016-10-12 PC procedure to return bank details for candidate
2017-01-17 PC provide flag to hide all details other than paye, to avoid
candidates being able to edit payment agencies details.
2017-09-26 PC include tax details
2017-10-24 PC alter size of tax parameters
2018-04-24 PC add column to hide tax type tab
2018-05-06 PC IW-503 only display last two digits of bank code
2018-10-10 MHS IW-456 multi-cand fix and tests
2019-4-9 MHS strip out rogue tax code rubbish

Tests:
  Valid pWebUserID without read permission
  Valid pWebUserID with read permission

Flag names:
  CandBankDetailsView

*/

/* TEST
NetTestSetup('');
insert into pay_employee
(Personid,bankname,banksortcode,BankAcName,BankAcNo,BankRef,secondaryagencyid) on existing update defaults off values
('TEST','TestBank','99-99-99','TestTest','09988776','TestRef','TEST');
insert into iqxnetright (IQXNetRightID,Description,sortorder) on existing
update defaults off values ('CANDBANKDETAILSVIEW','View candidate bank
details',998);
insert into iqxnetrightallowed
(iqxnetrightid,ixxnetuserclassid,id,maintainonweb) on existing update
defaults off values ('CANDBANKDETAILSVIEW','CANDIDATE','*',1);
select * from NetCandidateBankDetails(null);
```



```
expect EOF;
select * from NetCandidateBankDetails(null);
expect EOF;
insert into iqxnetrightassigned (iqxnetuserid,iqxnetrightid,assigned) on
existing update defaults off values
('test.candidate','candbankdetailsview',1);
select * from "NetCandidateBankDetails"("pWebUserID" = 'test.candidate');
expect
BankName=TestBank,BankSortCode=99-99-99,BankAcName=TestTest,BankAcNo=*****7
6,BankRef=TestRef;
delete from iqxnetrightassigned where iqxnetuserid='test.candidate' and
iqxnetrightid='candbankdetailsview';
*/
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netcandidatebankdetails

Last update: **2026/08/07 19:24**

