



pears.NetCandidateValidPersonID



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetCandidateValidPersonID"
IS
{CREATE FUNCTION pears."NetCandidateValidPersonID"( IN pWebUserID CHAR(20),
IN pPersonID CHAR(20) DEFAULT NULL )
RETURNS CHAR(20)
BEGIN
    DECLARE rv CHAR(20);
    SET pPersonID=NULLIF(TRIM(pPersonID),'');
    IF pPersonID IS NULL THEN -- Return a valid personid only if a unique one
is available
        IF (SELECT COUNT(*) FROM iqxnetuserlink l KEY JOIN person p WHERE
p.status<>'.' AND l.IQXNetUserID=pWebUserID)=1 THEN
            SET rv=(SELECT FIRST p.PersonID FROM iqxnetuserlink l KEY JOIN
person p WHERE p.status<>'.' AND l.IQXNetUserID=pWebUserID ORDER BY 1)
        END IF
    ELSE -- Validate the supplied personid
        SET rv=(SELECT FIRST PersonID FROM iqxnetuserlink WHERE
PersonID=pPersonID AND IQXNetUserID=pWebUserID ORDER BY 1)
    END IF;
    RETURN rv;
END

/* DOC
2018-10-19 MHS created for IW-456
2018-12-19 MHS now exclude archived records
*/

/* TEST
call NetTestSetup('');
select isnull(NetCandidateValidPersonID(null),'NULL');
expect NULL;
select isnull(NetCandidateValidPersonID('test.client'),'NULL');
expect NULL;
select isnull(NetCandidateValidPersonID('test.candidate'),'NULL');
expect TEST;
```



```
insert into iqxnetuserlink (iqxnetuserlinkid, personid, iqxnetuserid) values
('TEST_XX1','TEST', 'TEST.CANDIDATE');
select isnull(NetCandidateValidPersonID('test.candidate'),'NULL');
expect NULL;
select isnull(NetCandidateValidPersonID('test.candidate','TEST'),'NULL');
expect TEST;
delete from iqxnetuserlink where iqxnetuserlinkid='TEST_XX1';
*/
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netcandidatevalidpersonid

Last update: **2026/08/07 19:24**

