



pears.NetClientCandidateStatusUpdate



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetClientCandidateStatusUpdate"( IN "pWebUserID"
CHAR(20) )
RESULT( "value" CHAR(20),"descrip" CHAR(50),"IsFinal" CHAR(1) )
// IQXNet
BEGIN
    SELECT "status","name","final" FROM "status" WHERE "type" = 'R' AND
"allowsetonweb" = 1 ORDER BY "gridsortorder" ASC
END /* DOC
2016-12-08 PC supply a reason to update the progress of a candidate in a
placement

Inputs:
pWebUserID

Outputs:
value
descrip
IsFinal

Tests:
valid pWebUserID
*/
/* TEST
call NetTestSetup('');
insert into status (type,status,allowsetonweb,name,final,help,publishtoweb)
on existing update values ('R','~',1,'test',1,'test',1);
select top 1 * from NetClientCandidateStatusUpdate('test.client') where
value='~';
expect value=~ ,descrip=test,IsFinal=1;

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetClientCandidateStatusUpdate" IS
```



```
{CREATE PROCEDURE pears."NetClientCandidateStatusUpdate"(IN pWebUserID
CHAR(20))
RESULT(VALUE CHAR(20),descrip CHAR(50),IsFinal CHAR(1))
// IQXNet
BEGIN
    SELECT STATUS,name,final FROM STATUS WHERE TYPE='R' AND allowsetonweb=1
ORDER BY gridsortorder
END

/* DOC
2016-12-08 PC supply a reason to update the progress of a candidate in a
placement

Inputs:
    pWebUserID

Outputs:
    value
    descrip
    IsFinal

Tests:
    valid pWebUserID
*/

/* TEST
call NetTestSetup('');
insert into status (type,status,allowsetonweb,name,final,help,publishtoweb)
on existing update values ('R','~',1,'test',1,'test',1);
select top 1 * from NetClientCandidateStatusUpdate('test.client') where
value='~';
expect value=~ ,descrip=test,IsFinal=1;

*/
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netclientcandidatestatusupdate

Last update: 2026/08/07 19:24

