



pears.NetClientRequirementStatusFilter



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetClientRequirementStatusFilter"( IN "pWebUserID"
CHAR(20) )
RESULT( "value" CHAR(20),"descrip" CHAR(50) )
// IQXNet
BEGIN
    SELECT "status","name" FROM "status" WHERE "type" = 'v' AND
"allowsetonweb" = 1 ORDER BY "gridsortorder" ASC
END /* DOC
2016-12-08 PC supply a reason for filtering the Requirement List

Inputs:
pWebUserID

Outputs:
value
descrip

Tests:
invalid pWebUserID
valid pWebUserID
*/
/* TEST
call NetTestSetup('');
insert into status (type,status,name,help,allowsetonweb) on existing update
values ('V','~','test','test',1);
select * from NetClientRequirementStatusFilter(null);
expect value=~ ,descrip=test;
select * from NetClientRequirementStatusFilter('test.client');
expect value=~ ,descrip=test;

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetClientRequirementStatusFilter" IS
```



```
{CREATE PROCEDURE pears."NetClientRequirementStatusFilter"(IN pWebUserID
CHAR(20))
RESULT(VALUE CHAR(20),descrip CHAR(50))
// IQXNet
BEGIN
    SELECT STATUS,name FROM STATUS WHERE TYPE='v' AND allowsetonweb=1 ORDER
BY gridsortorder;
END

/* DOC
2016-12-08 PC supply a reason for filtering the Requirement List

Inputs:
    pWebUserID

Outputs:
    value
    descrip

Tests:
    invalid pWebUserID
    valid pWebUserID
*/

/* TEST
call NetTestSetup('');
insert into status (type,status,name,help,allowsetonweb) on existing update
values ('V','~','test','test',1);
select * from NetClientRequirementStatusFilter(null);
expect value=~,descrip=test;
select * from NetClientRequirementStatusFilter('test.client');
expect value=~,descrip=test;

*/
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netclientrequirementstatusfilter

Last update: 2026/08/07 19:24

