



pears.NetClientShiftOrderReasons



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetClientShiftOrderReasons" ( IN "pWebUserID"
CHAR(20) )
RESULT( "value" CHAR(20), "descrip" CHAR(50) )
//IQXNet
BEGIN
    SELECT "TempShiftOrderReasonID" AS "value",
        "Description" AS "descrip"
    FROM "tempshiftorderreason"
    ORDER BY "SortOrder" ASC
END /* DOC
2016-10-20 PC modify to include doc and test

inputs:
pWebUserID

outputs:
OrderReasonList

tests:
test delegated through NetOrderReasonList
invalid pWebUserID
valid pWebUserID

*/
/* TEST
call NetTestSetup('');
insert into tempshiftorderreason (tempshiftorderreasonid,description) on
existing update values ('TEST','test');
select descrip from NetClientShiftOrderReasons(null) where value='TEST';
expect descrip=test;

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetClientShiftOrderReasons"
```



```
IS
{CREATE PROCEDURE pears."NetClientShiftOrderReasons"( IN "pWebUserID"
CHAR(20) )
RESULT(VALUE CHAR(20),descrip CHAR(50))
//IQXNet
BEGIN
    SELECT
        TempShiftOrderReasonID AS VALUE,
        Description AS descrip
    FROM
        tempshiftorderreason
    ORDER BY
        SortOrder ASC
END

/* DOC
2016-10-20 PC modify to include doc and test

inputs:
    pWebUserID

outputs:
    OrderReasonList

tests:
    test delegated through NetOrderReasonList
    invalid pWebUserID
    valid pWebUserID

*/

/* TEST
call NetTestSetup('');
insert into tempshiftorderreason (tempshiftorderreasonid,description) on
existing update values ('TEST','test');
select descrip from NetClientShiftOrderReasons(null) where value='TEST';
expect descrip=test;

*/
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netclientshiftorderreasons

Last update: 2026/08/07 19:24



