



pears.NetDashboardObjectSet



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetDashboardObjectSet"( IN "pWebUserID"
CHAR(20),IN "pDashboardObjectID" CHAR(20) DEFAULT NULL,IN "pType" CHAR(50)
DEFAULT NULL,IN "pTitle" CHAR(250) DEFAULT NULL,IN "pDescriptor" long
VARCHAR DEFAULT NULL,IN "pShared" SMALLINT DEFAULT NULL,IN "pAccessLevel"
SMALLINT DEFAULT NULL,IN "pDashboard" SMALLINT DEFAULT NULL,IN "pHomePage"
SMALLINT DEFAULT NULL )
RESULT( "pResult" CHAR(250) )
// IQXWeb
BEGIN
    DECLARE "uStaffID" CHAR(20);
    SELECT "staffid" INTO "uStaffID" FROM "iqxnetuser" WHERE "iqxnetuserid" =
    "pWebUserID";
    IF "uStaffID" IS NULL THEN
        SELECT '99:~Permission denied';
        RETURN
    END IF;
    IF "pType" = 'DELETE' THEN
        DELETE FROM "DashboardObject" WHERE "DashboardObjectID" =
    "pDashboardObjectID" AND "StaffID" = "uStaffID";
        SELECT '0:~Success';
        RETURN
    END IF;
    IF "pDashboardObjectID" IS NULL THEN
        SET "pDashboardObjectID" = "uniquekey"(' ');
        INSERT INTO "DashboardObject"(
    "DashboardObjectID","StaffID","Type","Title","Descriptor","Shared","AccessLe
    vel" ) VALUES(
    "pDashboardObjectID","uStaffID","pType","pTitle","pDescriptor","pShared","is
    null"("pAccessLevel",0) )
    ELSE
        UPDATE "DashboardObject" SET "Title" =
    "isnull"("pTitle","Title"),"Descriptor" =
    "isnull"("pDescriptor","Descriptor"),"Shared" =
    "isnull"("pShared","Shared"),"AccessLevel" =
    "isnull"("pAccessLevel","AccessLevel") WHERE "DashboardObjectID" =
```



```
"pDashboardObjectID" AND "StaffID" = "uStaffID"
END IF;
IF "pDashboard" IS NOT NULL THEN
    INSERT INTO "DashboardDisplayedObject"(
"DashboardObjectID","StaffID","OnDashboard" ) ON existing UPDATE defaults
off VALUES( "pDashboardObjectID","uStaffID","pDashboard" )
END IF;
IF "pHomePage" IS NOT NULL THEN
    INSERT INTO "DashboardDisplayedObject"(
"DashboardObjectID","StaffID","OnHomePage" ) ON existing UPDATE defaults off
VALUES( "pDashboardObjectID","uStaffID","pHomePage" )
END IF;
DELETE FROM "DashboardDisplayedObject" WHERE "DashboardObjectID" =
"pDashboardObjectID" AND "StaffID" = "uStaffID" AND "OnDashboard" = 0 AND
"OnHomePage" = 0;
SELECT '0: '+'pDashboardObjectID'+ '~Success'
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetDashboardObjectSet" IS
{CREATE PROCEDURE pears.NetDashboardObjectSet( IN pWebUserID CHAR(20), IN
pDashboardObjectID CHAR(20) DEFAULT NULL, IN pType CHAR(50) DEFAULT NULL, IN
pTitle CHAR(250) DEFAULT NULL, IN pDescriptor long VARCHAR DEFAULT NULL, IN
pShared SMALLINT DEFAULT NULL, IN pAccessLevel SMALLINT DEFAULT NULL, IN
pDashboard SMALLINT DEFAULT NULL, IN pHomePage SMALLINT DEFAULT NULL)
RESULT(pResult CHAR(250))
// IQXWeb
BEGIN
    DECLARE uStaffID CHAR(20);
    SELECT staffid INTO uStaffID FROM ixqnetuser WHERE ixqnetuserid =
pWebUserID;
    IF uStaffID IS NULL THEN
        SELECT '99:~Permission denied';
        RETURN
    END IF;
    IF pType='DELETE' THEN
        DELETE FROM DashboardObject WHERE DashboardObjectID=pDashboardObjectID
AND StaffID=uStaffID;
        SELECT '0:~Success';
        RETURN;
    END IF;
    IF pDashboardObjectID IS NULL THEN
        SET pDashboardObjectID=uniquekey('');
        INSERT INTO DashboardObject
(DashboardObjectID,StaffID,TYPE,Title,Descriptor,Shared,AccessLevel) VALUES
(pDashboardObjectID,uStaffID,pType,pTitle,pDescriptor,pShared,isnull(pAccess
Level,0))
    ELSE
```



```
UPDATE DashboardObject SET Title=isnull(pTitle,Title),
Descriptor=isnull(pDescriptor,Descriptor), Shared=isnull(pShared,Shared),
AccessLevel=isnull(pAccessLevel,AccessLevel) WHERE
DashboardObjectID=pDashboardObjectID AND StaffID=uStaffID
END IF;
IF pDashboard IS NOT NULL THEN
    INSERT INTO DashboardDisplayedObject (DashboardObjectID, StaffID,
OnDashboard) ON existing UPDATE defaults off VALUES
(pDashboardObjectID,uStaffID,pDashboard);
END IF;
IF pHomePage IS NOT NULL THEN
    INSERT INTO DashboardDisplayedObject (DashboardObjectID, StaffID,
OnHomePage) ON existing UPDATE defaults off VALUES
(pDashboardObjectID,uStaffID,pHomePage);
END IF;
DELETE FROM DashboardDisplayedObject WHERE
DashboardObjectID=pDashboardObjectID AND StaffID=uStaffID AND OnDashboard=
AND OnHomePage=0;
SELECT '0: '+pDashboardObjectID+'~Success'
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netdashboardobjectset

Last update: 2026/08/07 19:24

