



pears.NetDebtorsDaySalesOutstanding



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetDebtorsDaySalesOutstanding" IS
{CREATE FUNCTION pears."NetDebtorsDaySalesOutstanding"( IN "pAccountCode"
CHAR(12),IN "DaysInPeriod" INTEGER,IN "CutoffDate" DATE )
RETURNS DECIMAL(10,2)
BEGIN
    DECLARE "Outst" DECIMAL(10,2);
    DECLARE "Sales" DECIMAL(10,2);
    DECLARE "dStart" DATE;
    SET "dStart" = "dateadd"("dd",-1*("daysinperiod"-1),"CutoffDate");
    SET "Outst" = (SELECT
"sum"("IQacDocumentOutstandingAmount"("DocumentID","CutOffDate")) FROM
"iqacdocument" WHERE "AccountCode" = "pAccountCode" AND "ledgerid" = 'Sales'
AND("fullyallocated" IS NULL OR "fullyallocated" > "CutOffDate"));
    SET "Sales" = (SELECT "sum"("amount") FROM "iqacdocument" WHERE "ledgerid"
= 'Sales' AND "accountcode" = "pAccountCode" AND "accountingdate" BETWEEN
"dstart" AND "cutoffdate" AND "documentclass" = 'Invoice');
    IF "isnull"("Sales",0) = 0 THEN
        RETURN NULL
    ELSE
        RETURN("Outst"/"sales")*"DaysInPeriod"
    END IF
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netdebtorsdaysalesoutstanding

Last update: 2026/08/07 19:24

