



pears.NetGetEmail



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetGetEmail" IS
{CREATE FUNCTION pears."NetGetEmail"( IN cpe CHAR(2),IN recid CHAR(20) )
RETURNS CHAR(250)
//IQXWeb
BEGIN
    DECLARE rv CHAR(250);
    SELECT FIRST REPLACE(phone.number,'*','') INTO rv FROM phone KEY JOIN
phonetype WHERE phone.who = recid AND phone.who = (IF cpe = 'E' THEN 'CP'
ELSE cpe endif) AND
    phonetype.name = 'E-mail' ORDER BY 1;
    RETURN(rv)
END

/* TEST
call NetTestSetup('');
delete from phone where phoneid like 'test%';
insert into phone (phoneid, phonetypeid, who, whoid, number) values
('Test1',(select top 1 phonetypeid from phonetype where name like 'E-Mail'
and contact=1),'CP','TEST','test@test.com');
insert into phone (phoneid, phonetypeid, who, whoid, number) values
('Test2',(select top 1 phonetypeid from phonetype where name like 'E-Mail'
and company=1),'C','TEST','test2@test.com');
select NetGetEmail(null,null);
expect;
select NetGetEmail('x','f99');
expect;
select isnull(NetGetEmail('x','TEST'),'empty');
expect empty;
select NetGetEmail('C','x');
expect;
select NetGetEmail('C','TEST');
expect test2@test.com;
select NetGetEmail('E','TEST');
expect test@test.com;
delete from phone where phoneid like 'test%';
```



```
*/  
  
/* DOC  
2016-08-25 PC tests and document  
2020-04-21 JW Rewritten for inlining.  
  
inputs:  
    cpe - phone.who  
    recid - phone.whooid  
  
outputs:  
    rv - return value  
  
tests:  
    null cpe and null recid  
    incorrect cpe incorrect recid  
    incorrect cpe correct recid  
    correct cpe (not E) incorrect recid  
    correct cpe (not E) correct recid  
    correct cpe (E) correct recid  
*/  
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netgetemail

Last update: **2026/08/07 19:24**

