pears.NetGetSwitches

Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetGetSwitches"( IN "pWebUserID" CHAR(20) )
RESULT( "pSwitches" CHAR(20) )
// IQXWeb
BEGIN
  SELECT top 1 "IQXNetSwitchID" FROM "IQXNetSwitch" WHERE "Value" = 1
END /* DOC
2017-11-07 GJ Created - Probably needs tweaking
2018-01-25 PC slightly tweaked

Inputs:
pWebUserID

Outputs:
pSwitches

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetGetSwitches" IS
{CREATE PROCEDURE pears."NetGetSwitches"( IN pWebUserID CHAR(20) )
RESULT( pSwitches CHAR(20) )
// IQXWeb
BEGIN
    SELECT top 1 IQXNetSwitchID FROM  IQXNetSwitch WHERE VALUE=1
END

/* DOC
2017-11-07 GJ Created - Probably needs tweaking
2018-01-25 PC slightly tweaked

Inputs:
    pWebUserID

Outputs:
    pSwitches
```

```
*/
}
```

From:
https://iqxusers.co.uk/iqxhelp/ - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netgetswitches

Last update: **2026/08/07 19:24**