



pears.NETITSPayslipsHours



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NETITSPayslipsHours"( IN "pWebUserID" CHAR(20), IN
"importID" CHAR(20) )
--RESULT()
// IQXWeb
// ITSPaySlip Proc
BEGIN
    SELECT *
      FROM "ITSPayslipHours"
     WHERE "ITSPayslipImportID" = "importID"
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NETITSPayslipsHours" IS
{CREATE PROCEDURE pears."NETITSPayslipsHours"( IN "pWebUserID" CHAR(20), IN
"importID" CHAR(20) )
--RESULT()
// IQXWeb
// ITSPaySlip Proc
BEGIN
    SELECT
        *
      FROM
        ITSPayslipHours
     WHERE
        ITSPayslipImportID=importID
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netitspayslipshours

Last update: 2026/08/07 19:24



