



pears.NetOwnerActionDialog



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerActionDialog"( IN "pWebUserID" CHAR(20),IN
"pObjectID" CHAR(20) DEFAULT NULL )
RESULT( "number" CHAR(200),"PhoneCapabilities" CHAR(20),"PhoneType"
CHAR(100) )
BEGIN
    DECLARE "NodeAddress" long VARCHAR;
    SET "NodeAddress" = (SELECT top 1 "addr1"+(IF "isnull"("Addr2",'') <> ''
THEN ', '+ "Addr2" endif)+(IF "isnull"("Addr3",'') <> '' THEN ', '+ "Addr3"
endif)+(IF "isnull"("Town",'') <> '' THEN ', '+ "Town" endif)+(IF
"isnull"("postcode",'') <> '' THEN ', '+ "postcode" endif) FROM "person"
WHERE "personid" = "pObjectID");
    IF "isnull"("NodeAddress",'') = '' THEN
        SET "NodeAddress" = (SELECT top 1 "addr1"+(IF "isnull"("Addr2",'') <> ''
THEN ', '+ "Addr2" endif)+(IF "isnull"("Addr3",'') <> '' THEN ', '+ "Addr3"
endif)+(IF "isnull"("Town",'') <> '' THEN ', '+ "Town" endif)+(IF
"isnull"("postcode",'') <> '' THEN ', '+ "postcode" endif) FROM "company" KEY
JOIN "employment" WHERE "employmentid" = "pObjectID")
    END IF;
    IF "isnull"("NodeAddress",'') = '' THEN
        SET "NodeAddress" = (SELECT top 1 "addr1"+(IF "isnull"("Addr2",'') <> ''
THEN ', '+ "Addr2" endif)+(IF "isnull"("Addr3",'') <> '' THEN ', '+ "Addr3"
endif)+(IF "isnull"("Town",'') <> '' THEN ', '+ "Town" endif)+(IF
"isnull"("postcode",'') <> '' THEN ', '+ "postcode" endif) FROM "company"
WHERE "companyid" = "pObjectID")
    END IF;
    SELECT DISTINCT "p"."number",
        (SELECT "list"("t"."capabilities" ORDER BY "t"."capabilities" ASC) AS
"PhoneCapabilities" FROM "phone" AS "ph" KEY JOIN "phonetype" AS "t" WHERE
"ph"."whoid" = "p"."whoid" AND "ph"."number" = "p"."number"),
        (SELECT "list"("t"."name" ORDER BY "t"."name" ASC) AS "PhoneType" FROM
"phone" AS "ph" KEY JOIN "phonetype" AS "t" WHERE "ph"."whoid" = "p"."whoid"
AND "ph"."number" = "p"."number")
    FROM "phone" AS "p"
    WHERE "whoid" = "pObjectID" UNION
    SELECT top 1(IF "isnull"("NodeAddress",'') <> '' THEN "NodeAddress"
```



```
endif),(IF "isnull"("NodeAddress",'') <> '' THEN 'A' endif),(IF
"isnull"("NodeAddress",'') <> '' THEN 'Address' endif)
END /* DOC
2016-08-20 PC

test:
select single entry phone
select double entry phone
select email
select person address
select company address
select contact address

*/
/* TEST
call NetTestSetup('');
update iqxnetuserlink set employmentid=null,personid=null where
IQXNetUserLinkID in
('test.agency','test.client','test.candidate','test.owner');
update iqxnetuserlink set employmentid='TEST',personid='TEST' where
IQXNetUserLinkID='test.candidate';
update person set
addr1='TestAddr1',addr2='TestAddr2',town='TestTown',postcode='XX9 9XX' where
personid='TEST';
select replace(replace(number,' ','!'),' ','~') as
A,replace(PhoneCapabilities,' ','!') as B,replace(PhoneType,' ','!') as C
from NetOwnerActionDialog('test.owner','test');
expect A=0499!999!995,B=D,C=Direct!Telephone;
expect A=0999!999!994,B=DS,C=Mobile;
expect A=test70@test.com,B=E,C=E-mail;
expect A=0999!999!993,B=F,C=Direct!Fax;
expect A=TestAddr1~!TestAddr2~!TestTown~!XX9!9XX,B=A,C=Address;
Expect EOF;
update person set addr1=null,addr2=null,town=null,postcode=null where
personid='TEST';
*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetOwnerActionDialog" IS
{CREATE PROCEDURE pears."NetOwnerActionDialog"(IN pWebUserID CHAR(20),IN
pObjectID CHAR(20) DEFAULT NULL)
RESULT(NUMBER CHAR(200),PhoneCapabilities CHAR(20),PhoneType CHAR(100))
BEGIN
    DECLARE NodeAddress long VARCHAR;
    SET NodeAddress=(SELECT top 1 addr1+(IF isnull(Addr2,'')!='' THEN ' ',
'+Addr2 endif)+(IF isnull(Addr3,'')!='' THEN ' ', '+Addr3 endif)+(IF
isnull(Town,'')!='' THEN ' ', '+Town endif)+(IF isnull(postcode,'')!='' THEN
', '+postcode endif) FROM person WHERE personid=pObjectID);
```



```
IF isnull(NodeAddress,'')='' THEN
    SET NodeAddress=(SELECT top 1 addr1+(IF isnull(Addr2,'')!='' THEN ' ',
'+Addr2 endif)+(IF isnull(Addr3,'')!='' THEN ' ', '+Addr3 endif)+(IF
isnull(Town,'')!='' THEN ' ', '+Town endif)+(IF isnull(postcode,'')!='' THEN
', '+postcode endif) FROM company KEY JOIN employment WHERE
employmentid=pObjectID);
END IF;
IF isnull(NodeAddress,'')='' THEN
    SET NodeAddress=(SELECT top 1 addr1+(IF isnull(Addr2,'')!='' THEN ' ',
'+Addr2 endif)+(IF isnull(Addr3,'')!='' THEN ' ', '+Addr3 endif)+(IF
isnull(Town,'')!='' THEN ' ', '+Town endif)+(IF isnull(postcode,'')!='' THEN
', '+postcode endif) FROM company WHERE companyid=pObjectID);
END IF;

SELECT DISTINCT p.number,
(SELECT list(t.capabilities ORDER BY t.capabilities) AS PhoneCapabilities
FROM phone ph KEY JOIN phonetype t WHERE ph.whoId=p.whoId AND
ph.number=p.number),
(SELECT list(t.name ORDER BY t.name) AS PhoneType FROM phone ph KEY JOIN
phonetype t WHERE ph.whoId=p.whoId AND ph.number=p.number)
FROM phone p
WHERE whoId=pObjectID
UNION
SELECT top 1 (IF isnull(NodeAddress,'')!='' THEN NodeAddress endif),(IF
isnull(NodeAddress,'')!='' THEN 'A' endif),(IF isnull(NodeAddress,'')!=''
THEN 'Address' endif)

END

/* DOC
2016-08-20 PC

test:
    select single entry phone
    select double entry phone
    select email
    select person address
    select company address
    select contact address

*/

/* TEST
call NetTestSetup('');
update iqxnetuserlink set employmentid=null,personid=null where
IQXNetUserLinkId in
('test.agency','test.client','test.candidate','test.owner');
update iqxnetuserlink set employmentid='TEST',personid='TEST' where
```



```
IQXNetUserLinkID='test.candidate';  
update person set  
addr1='TestAddr1',addr2='TestAddr2',town='TestTown',postcode='XX9 9XX' where  
personid='TEST';  
select replace(replace(number,' ','!'),',','~') as  
A,replace(PhoneCapabilities,' ','!') as B,replace(PhoneType,' ','!') as C  
from NetOwnerActionDialog('test.owner','test');  
expect A=0499!999!995,B=D,C=Direct!Telephone;  
expect A=0999!999!994,B=DS,C=Mobile;  
expect A=test70@test.com,B=E,C=E-mail;  
expect A=0999!999!993,B=F,C=Direct!Fax;  
expect A=TestAddr1~!TestAddr2~!TestTown~!XX9!9XX,B=A,C=Address;  
Expect EOF;  
update person set addr1=null,addr2=null,town=null,postcode=null where  
personid='TEST';  
*/  
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netowneractiondialog

Last update: **2026/08/07 19:24**

