



pears.NetOwnerAddToFavs



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerAddToFavs"( IN "pWebUserID" CHAR(20),IN
"pParent" CHAR(20),IN "pLinkID" CHAR(20),IN "pType" CHAR(1) )
/* RESULT( column_name column_type, ... ) */
BEGIN
  DECLARE "pStaffID" CHAR(20);
  SET "pStaffID" = (SELECT "staffid" FROM "iqxnetuser" WHERE "iqxnetuserid"
= "pWebUserID");
  IF "isnull"("pStaffID",'') = '' THEN
    SELECT '99:~invalid staff';
    RETURN
  END IF;
  IF "isnull"("pType",'') = '' THEN
    SELECT '98:~invalid type';
    RETURN
  END IF;
  INSERT INTO "Favourites"(
"FavouritesID","Parent","ID","Staffid","Description","Type" ) VALUES
( "uniquekey"('x'),"pParent","pLinkID","pStaffID",'',"pType" ) ;
  SELECT '0:~Success'
END /* DOC
2016-12-01 PC Doc and test
2018-08-27 PC improve error handling

Tests:
invalid pWebUserID
valid pWebUserID, pParent, pLinkID, invalid pType
valid pWebUserID, pParent, pLinkID, pType

*/
/* TEST
call NetTestSetup('');
update iqxnetuserlink set employmentid=null where IQXNetUserLinkID in
('test.client','test.agency','test.candidate','test.owner');
update iqxnetuserlink set employmentid='TEST' where
IQXNetUserLinkID='test.owner';
```



```
insert into Favourites (FavouritesID, Parent, ID, Staffid, Description,
Type) on existing update values ('TEST', null, null, 'TEST', '', 'H');
select * from NetOwnerAddToFavs(null,null,null,null);
expect 99*;
select * from NetOwnerAddToFavs('test.owner',null,null,null);
expect 98*;
select * from NetOwnerAddToFavs('test.owner','TEST','TEST','P');
expect 0*;
select * from favourites where staffID='TEST' and favouritesid != 'TEST'
order by FavouritesID asc;
expect Staffid=TEST,Type=H;

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetOwnerAddToFavs" IS
{CREATE PROCEDURE pears."NetOwnerAddToFavs"( IN "pWebUserID" CHAR(20), IN
"pParent" CHAR(20), IN "pLinkID" CHAR(20), IN "pType" CHAR(1) )
/* RESULT( column_name column_type, ... ) */
BEGIN
    DECLARE pStaffID CHAR(20);
    SET pStaffID=(SELECT staffid FROM iqxnetuser WHERE
iqxnetuserid=pWebUserID);
    IF isnull(pStaffID,'')='' THEN
        SELECT '99:~invalid staff';
        RETURN;
    END IF;
    IF isnull(pType,'')='' THEN
        SELECT '98:~invalid type';
        RETURN;
    END IF;
    INSERT INTO Favourites (FavouritesID, Parent, ID, Staffid, Description,
TYPE)
    VALUES (uniquekey('x'), pParent, pLinkID, pStaffID, '', pType);

    SELECT '0:~Success';
END

/* DOC
2016-12-01 PC Doc and test
2018-08-27 PC improve error handling

Tests:
    invalid pWebUserID
    valid pWebUserID, pParent, pLinkID, invalid pType
    valid pWebUserID, pParent, pLinkID, pType

*/
```



```
/* TEST
call NetTestSetup('');
update iqxnetuserlink set employmentid=null where IQXNetUserLinkID in
('test.client','test.agency','test.candidate','test.owner');
update iqxnetuserlink set employmentid='TEST' where
IQXNetUserLinkID='test.owner';
insert into Favourites (FavouritesID, Parent, ID, Staffid, Description,
Type) on existing update values ('TEST', null, null, 'TEST', '', 'H');
select * from NetOwnerAddToFavs(null,null,null,null);
expect 99*;
select * from NetOwnerAddToFavs('test.owner',null,null,null);
expect 98*;
select * from NetOwnerAddToFavs('test.owner','TEST','TEST','P');
expect 0*;
select * from favourites where staffID='TEST' and favouritesid != 'TEST'
order by FavouritesID asc;
expect Staffid=TEST,Type=H;

*/
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netowneraddtofavs

Last update: **2026/08/07 19:24**

