pears.NetOwnerAggregateSearch

Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerAggregateSearch"( IN "pWebUserID"
CHAR(20),IN "SearchValue" CHAR(20) DEFAULT '%',IN "SearchCategory" CHAR(5)
DEFAULT NULL,IN "pSlice" INTEGER DEFAULT 1,IN "pSliceSize" INTEGER DEFAULT
20 )
RESULT( "ObjectID" CHAR(20),"ObjectName" CHAR(60),"Town"
CHAR(100),"JobTitle" CHAR(60),"Status" CHAR(10),"companyName"
CHAR(60),"Alert" CHAR(255),"IsFavourite" INTEGER )
BEGIN
  IF "length"("isnull"("SearchValue",'')) = 0 THEN
    SELECT '~','','','','','','',0;
    RETURN
  END IF;
  SELECT "Employmentid","name","address","jobtitle",'Contact' AS
"status","companyname","alert","isfavourite" FROM
"pears"."NetOwnerContactSearch"("pWebUserID" = "pWebUserID","SearchValue" =
"SearchValue","pSlice" = "pSlice","pSliceSize" = "pSliceSize") UNION
  SELECT "companyid","name","address",'' AS "Jobtitle",'Company' AS
"status",'',"alert","isfavourite" FROM
"pears"."NetOwnerCompanySearch"("pWebUserID" = "pWebUserID","SearchValue" =
"SearchValue","pSlice" = "pSlice","pSliceSize" = "pSliceSize") UNION
  SELECT "personid","name","address",'' AS "Jobtitle",'Candidate' AS
"status",'',"alert","isfavourite" FROM
"pears"."NetOwnerCandidateSearch"("pWebUserID" = "pWebUserID","SearchValue"
= "SearchValue","pSlice" = "pSlice","pSliceSize" = "pSliceSize")
    ORDER BY "name" ASC
END /* DOC
2016-09-19 PC alter routine to allow search, and paging

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetOwnerAggregateSearch" IS
{CREATE PROCEDURE pears."NetOwnerAggregateSearch"(IN "pWebUserID"
CHAR(20),IN "SearchValue" CHAR(20) DEFAULT '%',IN SearchCategory CHAR(5)
DEFAULT NULL,IN pSlice INTEGER DEFAULT 1, IN pSliceSize INTEGER DEFAULT 20 )
```

```
RESULT(ObjectID CHAR(20),ObjectName CHAR(60),Town CHAR(100),JobTitle
CHAR(60),STATUS CHAR(10),companyName CHAR(60),Alert CHAR(255),IsFavourite
INTEGER )
BEGIN
    IF LENGTH(isnull(SearchValue,''))=0 THEN
        SELECT '~','','','','','','',0;
        RETURN;
    END IF;
   SELECT Employmentid,name,address,jobtitle,'Contact' AS
STATUS,companyname,alert,isfavourite FROM
"pears"."NetOwnerContactSearch"("pWebUserID" = pWebUserID,"SearchValue" =
SearchValue,"pSlice" = pSlice,"pSliceSize" = pSliceSize)
   UNION
   SELECT companyid,name,address,'' AS Jobtitle,'Company' AS
STATUS,'',alert,isfavourite FROM
"pears"."NetOwnerCompanySearch"("pWebUserID" = pWebUserID,"SearchValue" =
SearchValue,"pSlice" = pSlice,"pSliceSize" = pSliceSize)
   UNION
   SELECT personid,name,address,'' AS Jobtitle,'Candidate' AS
STATUS,'',alert,isfavourite FROM
"pears"."NetOwnerCandidateSearch"("pWebUserID" = pWebUserID,"SearchValue" =
SearchValue,"pSlice" = pSlice,"pSliceSize" = pSliceSize)
   ORDER BY name ASC
END

/* DOC
2016-09-19 PC alter routine to allow search, and paging

*/
}
```

From:
https://iqxusers.co.uk/iqxhelp/ - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netowneraggregatesearch

Last update: **2026/08/07 19:24**