



pears.NetOwnerDashboardDiaryCountWeek



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerDashboardDiaryCountWeek"( IN "pWebUserID"
CHAR(20) )
RESULT( "thisweeksevents" CHAR(5) )
BEGIN
    SELECT "COUNT"() AS "thisweeksevents"
    FROM "diary" AS "D"
    KEY JOIN "staff" AS "S"
    LEFT OUTER JOIN "iqxnetuser" AS "U"
    WHERE "U"."iqxnetuserid" = "pWebUserID"
    AND "dateformat"("d"."diaryfrom",'yyyy-mm-dd') >= "dateformat"((SELECT
"dateadd"("dd",("datepart"("caldayofweek","today"()-1)*-1,"today"())), 'yyyy-
mm-dd')
    AND "dateformat"("d"."diaryto",'yyyy-mm-dd') <= "dateformat"((SELECT
"dateadd"("dd",(7-"datepart"("caldayofweek","today"())), "today"())), 'yyyy-
mm-dd')
END /* DOC
2017-03-23 | counts the number of events this week
*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetOwnerDashboardDiaryCountWeek" IS
{CREATE PROCEDURE pears."NetOwnerDashboardDiaryCountWeek"(IN pWebUserID
CHAR(20))
RESULT(thisweeksevents CHAR(5))
BEGIN
    SELECT
        COUNT(*) AS thisweeksevents
    FROM
        diary D
        KEY JOIN staff S
        LEFT JOIN iqxnetuser U
    WHERE
        U.iqxnetuserid=pWebUserID
    AND
```



```
        dateformat(d.diaryfrom, 'yyyy-mm-dd') >= dateformat((SELECT
dateadd(dd,(datepart (caldayofweek,today(*))-1)*-1,today(*))), 'yyyy-mm-dd')
    AND
        dateformat(d.diaryto, 'yyyy-mm-dd') <= dateformat((SELECT
dateadd(dd,(7-datepart (caldayofweek,today(*))),today(*))), 'yyyy-mm-dd')
    END

/* DOC
    2017-03-23 | counts the number of events this week
*/
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netownerdashboarddiarycountweek

Last update: **2026/08/07 19:24**

