



pears.NetOwnerSettingsGetRight



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerSettingsGetRight"( IN "pWebUserID"
CHAR(20) )
RESULT( "rightID" CHAR(255),"description" long VARCHAR )
// IQXWeb
BEGIN
    IF NOT "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
        SELECT "IQXNetRightID" AS "rightID","Description" AS "description" FROM
"IQXNetRight"
        ORDER BY "SortOrder" ASC
    ELSE
        SELECT '99:~Permission denied',''
    END IF
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetOwnerSettingsGetRight"
IS
{CREATE PROCEDURE pears."NetOwnerSettingsGetRight"( IN "pWebUserID"
CHAR(20))
RESULT( "rightID" CHAR(255),"description" long VARCHAR )
// IQXWeb
BEGIN
    IF NOT "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
        SELECT IQXNetRightID AS rightID, Description AS description FROM
IQXNetRight
        ORDER BY SortOrder
    ELSE
        SELECT '99:~Permission denied', '';
    END IF;
END
}
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netownersettingsgetright

Last update: **2026/08/07 19:24**

