



pears.NetOwnerSettingsGetRightDefault



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerSettingsGetRightDefault"( IN "pWebUserID"
CHAR(20) )
RESULT( "rightID" CHAR(255),"userClass" CHAR(255) )
BEGIN
    IF NOT "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
        SELECT "IQXNetRightID" AS "rightID","IQXNetUserClassID" AS "userClass"
FROM "IQXNetRightDefault"
    ELSE
        SELECT '99:~Permission denied',''
    END IF
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetOwnerSettingsGetRightDefault" IS
{CREATE PROCEDURE pears."NetOwnerSettingsGetRightDefault"( IN "pWebUserID"
CHAR(20))
RESULT( "rightID" CHAR(255),"userClass" CHAR(255) )
BEGIN
    IF NOT "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
        SELECT IQXNetRightID AS rightID, IQXNetUserClassID AS userClass FROM
IQXNetRightDefault
    ELSE
        SELECT '99:~Permission denied', '';
    END IF;
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netownersettingsgetrightdefault

Last update: 2026/08/07 19:24



