



pears.NetOwnerSettingsGetSwitches



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerSettingsGetSwitches"( IN "pWebUserID"
CHAR(20) )
RESULT( "name" CHAR(255),"description" long VARCHAR,"value" SMALLINT )
BEGIN
    IF NOT "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
        SELECT "IQXNetSwitchID" AS "name","Description" AS "description","Value"
AS "value" FROM "pears"."IQXNetSwitch"
        ORDER BY "name" ASC
    ELSE
        SELECT '99:~Permission denied',' ',' '
    END IF
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetOwnerSettingsGetSwitches" IS
{CREATE PROCEDURE pears."NetOwnerSettingsGetSwitches"( IN "pWebUserID"
CHAR(20))
RESULT( "name" CHAR(255),"description" long VARCHAR,"value" SMALLINT )
BEGIN
    IF NOT "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
        SELECT IQXNetSwitchID AS name, Description AS description, VALUE AS
VALUE FROM "pears"."IQXNetSwitch"
        ORDER BY name
    ELSE
        SELECT '99:~Permission denied', ' ', ' ';
    END IF;
END
}
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netownersettingsgetswitches

Last update: **2026/08/07 19:24**

