



pears.NetOwnerSettingsSaveRightsAssigned



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerSettingsSaveRightsAssigned"( IN
"pWebUserID" CHAR(20),IN "rightID" CHAR(50),IN "userID" CHAR(20),IN
"newValue" INTEGER )
RESULT( "pResult" CHAR(255) )
BEGIN
  IF "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
    SELECT '99:~Permission denied'
  ELSE
    DELETE FROM "IQXNetRightAssigned" WHERE "IQXNetUserID" = "userID" AND
"IQXNetRightID" = "rightID";
    IF NOT "newValue" = 0 THEN
      INSERT INTO "IQXNetRightAssigned" VALUES
        ( "userID","rightID","newValue" )
    END IF;
    SELECT '0:~Success'
  END IF
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetOwnerSettingsSaveRightsAssigned" IS
{CREATE PROCEDURE pears."NetOwnerSettingsSaveRightsAssigned"( IN
"pWebUserID" CHAR(20), IN "rightID" CHAR(50), IN "userID" CHAR(20), IN
"newValue" INTEGER)
RESULT(pResult CHAR(255) )
BEGIN
  IF "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
    SELECT '99:~Permission denied';
  ELSE
    DELETE FROM IQXNetRightAssigned WHERE IQXNetUserID = userID AND
IQXNetRightID = rightID;
    IF NOT "newValue" = 0 THEN
      INSERT INTO IQXNetRightAssigned
        VALUES(userID, rightID, newValue)
    END IF;
```



```
SELECT '0:~Success';  
END IF;  
END  
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netownersettingssaverightsassigned

Last update: **2026/08/07 19:24**

