



# pears.NetOwnerSettingsSaveRightsDefault



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

## Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerSettingsSaveRightsDefault"( IN
"pWebUserID" CHAR(20),IN "assignByDefault" INTEGER,IN "rightID" CHAR(50),IN
"userClass" CHAR(50) )
RESULT( "pResult" CHAR(255) )
BEGIN
  IF "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
    SELECT '99:~Permission denied'
  ELSE
    DELETE FROM "IQXNetRightDefault" WHERE "IQXNetRightID" = "rightID" AND
"IQXNetUserClassID" = "userClass";
    IF "assignByDefault" = 1 THEN
      INSERT INTO "IQXNetRightDefault" VALUES
        ( "rightID","userClass",'*' )
    END IF;
    SELECT '0:~Success'
  END IF
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetOwnerSettingsSaveRightsDefault" IS
{CREATE PROCEDURE pears."NetOwnerSettingsSaveRightsDefault"( IN "pWebUserID"
CHAR(20), IN "assignByDefault" INTEGER, IN "rightID" CHAR(50), IN
"userClass" CHAR(50) )
RESULT(pResult CHAR(255) )
BEGIN
  IF "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
    SELECT '99:~Permission denied';
  ELSE
    DELETE FROM IQXNetRightDefault WHERE IQXNetRightID = rightID AND
IQXNetUserClassID = userClass;
    IF assignByDefault = 1 THEN
      INSERT INTO IQXNetRightDefault
        VALUES (rightID, userClass, '*')
    END IF;
```



```
SELECT '0:~Success';  
END IF;  
END  
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

[https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears\\_netownersettings saverightsdefault](https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netownersettings saverightsdefault)

Last update: **2026/08/07 19:24**

