



pears.NetOwnerSettingsSaveSwitches



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetOwnerSettingsSaveSwitches"( IN "pWebUserID"
CHAR(20),IN "switchID" CHAR(50),IN "newValue" INTEGER )
RESULT( "pResult" CHAR(255) )
BEGIN
  IF "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
    SELECT '99:~Permission denied'
  ELSE
    UPDATE "IQXNetSwitch"
      SET "Value" = "newValue"
      WHERE "IQXNetSwitchID" = "switchID";
    SELECT '0:~Success'
  END IF
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetOwnerSettingsSaveSwitches" IS
{CREATE PROCEDURE pears."NetOwnerSettingsSaveSwitches"( IN "pWebUserID"
CHAR(20), IN "switchID" CHAR(50), IN "newValue" INTEGER)
RESULT(pResult CHAR(255) )
BEGIN
  IF "IQXNetHasPermission"("pWebUserID",'APIDESIGN') = 0 THEN
    SELECT '99:~Permission denied';
  ELSE
    UPDATE IQXNetSwitch
      SET VALUE = newValue
      WHERE IQXNetSwitchID = switchID;

    SELECT '0:~Success';
  END IF;
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netownersettingssaveswitches

Last update: **2026/08/07 19:24**

