



pears.NetPersonProfileSet



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetPersonProfileSet"( IN "pWebUserID" CHAR(20),IN
"ppersonid" CHAR(20),IN "pdob" CHAR(20) DEFAULT 'NOT-SET',IN "phomephone"
CHAR(250) DEFAULT 'NOT-SET',IN "pemail" CHAR(250) DEFAULT 'NOT-SET',IN
"pOLDdob" CHAR(20) DEFAULT 'NOT-SET',IN "pOLDhomephone" CHAR(250) DEFAULT
'NOT-SET',IN "pOLDemail" CHAR(250) DEFAULT 'NOT-SET' )
RESULT( "pResult" CHAR(250) )
BEGIN
    DECLARE "dateofbirth" DATE;
    IF NOT "ppersonid" = any(SELECT "personid" FROM "iqxnetuserlink" WHERE
"iqxnetuserid" = "pwebuserid") THEN
        SELECT '99:~Permission denied';
        RETURN
    END IF;
    IF "isnull"("pdob",'') <> "isnull"("pOLDdob",'') THEN
        SET "dateofbirth" = "IQXNetStringToDate"("pdob");
        IF "trim"("isnull"("pdob",'')) <> '' AND "dateofbirth" IS NULL THEN
            SELECT '1:~Invalid date of birth';
            RETURN
        END IF;
        UPDATE "person" SET "dob" = "dateofbirth" WHERE "personid" = "ppersonid"
    END IF;
    IF "isnull"("phomephone",'') <> "isnull"("pOLDhomephone",'') THEN
        CALL "setphone"('P','Home Telephone',"ppersonid","phomephone")
    END IF;
    IF "isnull"("pemail",'') <> "isnull"("pOLDemail",'') THEN
        CALL "setphone"('P','E-mail',"ppersonid","pemail");
        UPDATE "iqxnetuserlink" KEY JOIN "iqxnetuser" SET
"iqxnetuser"."emailaddress" = "pemail" WHERE "iqxnetuserlink"."personid" =
"ppersonid"
    END IF;
    SELECT '0:~Success'
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetPersonProfileSet" IS
```



```
{CREATE PROCEDURE pears."NetPersonProfileSet"( IN "pWebUserID" CHAR(20),IN
"ppersonid" CHAR(20),IN "pdob" CHAR(20) DEFAULT 'NOT-SET',IN "phomephone"
CHAR(250) DEFAULT 'NOT-SET',IN "pemail" CHAR(250) DEFAULT 'NOT-SET',IN
"pOLDdob" CHAR(20) DEFAULT 'NOT-SET',IN "pOLDhomephone" CHAR(250) DEFAULT
'NOT-SET',IN "pOLDemail" CHAR(250) DEFAULT 'NOT-SET' )
RESULT( "pResult" CHAR(250) )
BEGIN
  DECLARE "dateofbirth" DATE;
  IF NOT "ppersonid" = any(SELECT "personid" FROM "iqxnetuserlink" WHERE
"iqxnetuserid" = "pwebuserid") THEN
    SELECT '99:~Permission denied';
    RETURN
  END IF;
  IF "isnull"("pdob",'') <> "isnull"("pOLDdob",'') THEN
    SET "dateofbirth" = "IQXNetStringToDate"("pdob");
    IF "trim"("isnull"("pdob",'')) <> '' AND "dateofbirth" IS NULL THEN
      SELECT '1:~Invalid date of birth';
      RETURN
    END IF;
    UPDATE "person" SET "dob" = "dateofbirth" WHERE "personid" = "ppersonid"
  END IF;
  IF "isnull"("phomephone",'') <> "isnull"("pOLDhomephone",'') THEN
    CALL "setphone"('P','Home Telephone',"ppersonid","phomephone")
  END IF;
  IF "isnull"("pemail",'') <> "isnull"("pOLDemail",'') THEN
    CALL "setphone"('P','E-mail',"ppersonid","pemail");
    UPDATE "iqxnetuserlink" KEY JOIN "iqxnetuser" SET
    "iqxnetuser"."emailaddress" = "pemail" WHERE "iqxnetuserlink"."personid" =
    "ppersonid"
  END IF;
  SELECT '0:~Success'
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netpersonprofilesset

Last update: **2026/08/07 19:24**

