



pears._NetPushNotificationsDeviceRemove



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."_NetPushNotificationsDeviceRemove"( IN
"pWebUserID" CHAR(20),IN "pDeviceID" CHAR(20) )
RESULT( "pResult" CHAR(255) )
BEGIN
    DELETE FROM "PushNotificationDevice" WHERE "PushNotificationDeviceID" =
"pDeviceID" AND "WebUserID" = "pWebUserID";
    SELECT '0:~Success'
END /* DOC

2019-10-23 GJ Creation.

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."_NetPushNotificationsDeviceRemove" IS
{CREATE PROCEDURE pears."_NetPushNotificationsDeviceRemove"( IN pWebUserID
CHAR(20), IN pDeviceID CHAR(20))
RESULT(pResult CHAR(255) )
BEGIN
    DELETE FROM PushNotificationDevice WHERE PushNotificationDeviceID =
pDeviceID AND WebUserID = pWebUserID;

    SELECT '0:~Success';
END

/* DOC

2019-10-23 GJ Creation.

*/
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netpushnotificationsdeviceremove

Last update: **2026/08/07 19:24**

