



pears._NetPushNotificationsDevices



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."_NetPushNotificationsDevices"( IN "pWebUserID"
CHAR(20) )
RESULT( "PushNotificationDeviceID" CHAR(20),"DeviceName"
CHAR(100),"DeviceType" SMALLINT,"WhenCreated" "datetime" )
BEGIN
    SELECT "PushNotificationDeviceID",
        "DeviceName",
        "DeviceType",
        "WhenCreated"
    FROM "PushNotificationDevice"
    WHERE "WebUserID" = "pWebUserID"
END /* DOC
```

2019-10-04 GJ Creation.

```
*/
GO
```

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."_NetPushNotificationsDevices" IS
{CREATE PROCEDURE pears."_NetPushNotificationsDevices"( IN pWebUserID
CHAR(20) )
RESULT("PushNotificationDeviceID" CHAR(20), "DeviceName" CHAR(100),
"DeviceType" SMALLINT, "WhenCreated" datetime )
BEGIN
    SELECT
        PushNotificationDeviceID,
        DeviceName,
        DeviceType,
        WhenCreated
    FROM
        PushNotificationDevice
    WHERE
        WebUserID = pWebUserID;
END
```



```
/* DOC
```

```
2019-10-04 GJ Creation.
```

```
*/  
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netpushnotificationsdevices

Last update: **2026/08/07 19:24**

