



pears.NetQuestionGroupCountForDepartment



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetQuestionGroupCountForDepartment" ( IN
"pWebUserID" CHAR(20),IN "pDepartmentID" CHAR(20) )
RESULT( "pCount" INTEGER )
// IQXWeb
BEGIN
    SELECT "count"()
    FROM "IQXNetTagGroup"
    WHERE "iqxnettaggroupid" LIKE "isnull"("pDepartmentID",'')+ '_%'
END /* DOC
2017-08-15 PC count question groups for departments where department group
id has a structure including "_9"

*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE
"pears"."NetQuestionGroupCountForDepartment" IS
{CREATE PROCEDURE pears."NetQuestionGroupCountForDepartment"(IN pWebUserID
CHAR(20), IN pDepartmentID CHAR(20))
RESULT(pCount INTEGER)
// IQXWeb
BEGIN
    SELECT
        COUNT(*)
    FROM
        IQXNetTagGroup
    WHERE
        iqxnettaggroupid LIKE isnull(pDepartmentID,'')+ '_%'
END

/* DOC
2017-08-15 PC count question groups for departments where department group
id has a structure including "_9"
```



* /
}

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netquestiongroupcountfordepartment

Last update: **2026/08/07 19:24**

