



pears.NetReports



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetReports"( IN "pWebUserID" CHAR(20) )
RESULT( "ReportTitle" CHAR(200),"ReportSource" CHAR(100),"ReportParams" long
VARCHAR )
BEGIN
    SELECT "r"."Description" AS "ReportTitle","r"."DBProcedure" AS
"ReportSource",
    (SELECT "list"("parm_name" ORDER BY "parm_id" ASC) FROM "sysprocparm"
KEY JOIN "sysprocedure"
    WHERE "proc_name" = "r"."DBProcedure" AND "parm_mode_in" = 'Y' AND
"parm_name" <> 'pWebUserID') AS "ReportParams"
    FROM "iqxnetreport" AS "r" KEY JOIN "iqxnetuserclass" KEY JOIN
"iqxnetuser"
    WHERE "iqxnetuser"."iqxnetuserid" = "pWebUserID" AND("r"."IQXNetRightID"
IS NULL OR "iqxnethaspermission"("pWebUserID","r"."IQXNetRightID") > 0)
    ORDER BY "r"."sortorder" ASC,"r"."iqxnetreportid" ASC
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetReports" IS
{CREATE PROCEDURE pears.NetReports(IN pWebUserID CHAR(20))
RESULT(ReportTitle CHAR(200),ReportSource CHAR(100),ReportParams long
VARCHAR)
BEGIN
    SELECT r.Description AS ReportTitle,r.DBProcedure AS ReportSource,
    (SELECT list(parm_name ORDER BY parm_id ASC) FROM sysprocparm KEY JOIN
sysprocedure
    WHERE proc_name = r.DBProcedure AND parm_mode_in = 'Y' AND parm_name
<> 'pWebUserID') AS ReportParams
    FROM iqxnetreport AS r KEY JOIN iqxnetuserclass KEY JOIN iqxnetuser
    WHERE iqxnetuser.iqxnetuserid = pWebUserID AND(r.IQXNetRightID IS NULL
OR iqxnethaspermission(pWebUserID,r.IQXNetRightID) > 0) ORDER BY
    r.sortorder ASC,r.iqxnetreportid ASC
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netreports

Last update: **2026/08/07 19:24**

