



pears.NetResetPassword



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."NetResetPassword"( IN "pWebUserID" CHAR(20),IN
@token CHAR(100) )
RESULT( "Token" CHAR(100),"WhenCreated" TIMESTAMP )
// IQXWeb
BEGIN
    SELECT "BASE64_DECODE"(@token),
        "WhenCreated"
    FROM "IQXNetPasswordChangeRequest"
    WHERE "Token" = @Token
    AND "Sent" = 1
END /* TEST

*/
/* DOC
15-01-2019 GJ Created
*/
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NetResetPassword" IS
{CREATE PROCEDURE pears."NetResetPassword"(IN pWebUserID CHAR(20),IN @token
CHAR(100))
RESULT(Token CHAR(100), WhenCreated TIMESTAMP)
// IQXWeb
BEGIN
    SELECT
        BASE64_DECODE(@token),
        WhenCreated
    FROM
        IQXNetPasswordChangeRequest
    WHERE
        Token = @Token
    AND
        Sent = 1
END
```



```
/* TEST  
  
*/  
  
/* DOC  
   15-01-2019 GJ Created  
*/  
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_netresetpassword

Last update: **2026/08/07 19:24**

