pears.NotificationICS

Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."NotificationICS" IS
{CREATE FUNCTION NotificationICS
(IN "pTemplateID" CHAR(50),IN "pRecipientType" CHAR(20),IN "pPersonID"
CHAR(20), IN "pVacancyID" CHAR(20),IN "pCompanyID" CHAR(20),IN "pDivisionID"
CHAR(20),IN "pProgressID" CHAR(20), IN "pDiaryID" CHAR(20) )
RETURNS long VARCHAR
BEGIN
  DECLARE "rv" long VARCHAR;
  DECLARE @clientcode CHAR(12);
  DECLARE @TransportType CHAR(20);
  DECLARE @starttime TIMESTAMP;
  DECLARE @InterviewTime TIME;
  DECLARE @Notes long VARCHAR;
  DECLARE @description VARCHAR(200);
  DECLARE @Location VARCHAR(200);
  DECLARE @uid CHAR(20);
  SET "rv" = '';
 IF (@starttime  IS NOT NULL) AND (isnull(@description,'')<>'') THEN
/*  set "rv" = (select
"createicsfile"(@uid,@Location,@notes,@starttime,@starttime,@description,5,0
,0,''))*/
  END IF;
  RETURN "RV";
END
}
```

From:
https://iqxusers.co.uk/iqxhelp/ - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_notificationics

Last update: **2026/08/07 19:24**