



pears.PostCodePart



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."PostCodePart" IS
{CREATE FUNCTION PostCodePart
```

```
/* Application Maintained Function / Procedure - DO NOT EDIT*/
```

```
( IN postcode CHAR(20),IN part CHAR(20) )
RETURNS CHAR(20)
deterministic
BEGIN
    DECLARE i INTEGER;
    DECLARE area CHAR(20);
    SET postcode = TRIM(postcode);
    SET i = patindex('%[0-9]%',postcode);
    IF i = 0 THEN
        RETURN NULL
    END IF;
    SET area = substr(postcode,1,i-1);
    IF part = 'area' THEN
        RETURN area
    END IF;
    SET postcode = stuff(postcode,1,i-1,NULL);
    SET i = patindex('%[^0-9]%',postcode);
    IF part = 'district' THEN
        RETURN area+"left"(substr(postcode,1,i-1),2)
    END IF
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_postcodepart

Last update: 2026/08/07 19:24



