



pears.SetQuestDate



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."SetQuestDate"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "stagloc" CHAR(3),IN "stagid" CHAR(3),IN "sparentid" CHAR(20),IN  
    "dvalue" DATE )  
BEGIN  
    CALL  
    "setquestanswer"("stagloc","stagid",NULL,"sparentid","dateformat"("dvalue",'  
    yyyy-mm-dd'))  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."SetQuestDate" IS  
{CREATE PROCEDURE SetQuestDate  
  
/* Application Maintained Function / Procedure - DO NOT EDIT*/  
  
(IN stagloc CHAR(3),IN stagid CHAR(3),IN sparentid CHAR(20),IN dvalue DATE)  
BEGIN  
    CALL setquestanswer(stagloc,stagid,NULL,sparentid,dateformat(dvalue,'yyyy-  
    mm-dd'))  
END  
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_setquestdate

Last update: 2026/08/07 19:24

