



pears.TempVacancyShiftMatch



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."TempVacancyShiftMatch" IS
{CREATE FUNCTION TempVacancyShiftMatch( IN @PersonID CHAR(20),IN @VacancyID
CHAR(20) )
RETURNS DOUBLE
BEGIN
    DECLARE "rv" DOUBLE;
    SET "rv"
        = "DistanceBetweenPostCodes"(
            (SELECT "Person"."PostCode" FROM "Person" WHERE "Person"."PersonID" =
@PersonID),
            (SELECT "isnull"("vacancy"."postcode","company"."postcode") FROM
"Vacancy" KEY JOIN "Employment" KEY JOIN "Company" WHERE
"Vacancy"."VacancyID" = @VacancyID), 'Mi');
    IF "rv" < 1 THEN
        RETURN "round"("rv",1)
    ELSE RETURN "round"("rv",0)
    END IF
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_tempvacancyshiftmatch

Last update: 2026/08/07 19:24

