



pears.WPKLocalSwitchValue



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."WPKLocalSwitchValue" IS
{CREATE FUNCTION WPKLocalSwitchValue

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN SwitchID CHAR(20),IN SwitchLocation CHAR(20),IN SwitchSource CHAR(1),IN
SwitchLocked SMALLINT,IN SwitchLocalisable SMALLINT)
RETURNS long VARCHAR
BEGIN
    DECLARE rv long VARCHAR;
    SET rv=NULL;
    IF switchlocked = 1 OR switchsource NOT IN('L','P') THEN -- Only unlocked
Literal and Params switches can be over-ridden in this way
        RETURN rv
    END IF;
    IF switchlocation IS NOT NULL AND switchlocalisable = 1 THEN
        SELECT FIRST VALUE INTO rv FROM wpkglobalswitchsetting WHERE
wpkglobalswitchid = switchid AND location = switchlocation
    END IF;
    IF switchsource = 'L' AND rv IS NULL THEN -- Params continue to have their
global value stored in the params table
        SELECT FIRST VALUE INTO rv FROM wpkglobalswitchsetting WHERE
wpkglobalswitchid = switchid AND location = 'Global'
    END IF;
    RETURN rv
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_wpklocalswitchvalue

Last update: 2026/08/07 19:24



