



pears.agencydetails



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Branch details. A branch usually represents a physical location.

Columns

Column	Type	Null	Default	Comment
agencyid	char(20)	NOT NULL		
name	char(30)	NULL		
defaultreportdirectory	char(100)	NULL		
wpdocdirectory	char(100)	NULL		
currency	char(3)	NULL		
AddressEtc1	long varchar	NULL		
AddressEtc2	long varchar	NULL		
AddressEtc3	long varchar	NULL		
AddressEtc4	long varchar	NULL		
AddressEtc5	long varchar	NULL		
AddressEtc6	long varchar	NULL		
Analysis	char(50)	NULL		
divisionid	char(20)	NULL		
docstoragefolder	char(100)	NULL		
SMTPServer	char(20)	NULL		
IMAPServer	char(20)	NULL		
Extra1	long varchar	NULL		
Extra2	long varchar	NULL		
Extra3	long varchar	NULL		
IQXNetEmailDetailsID	char(20)	NULL		

Primary Key

- agencyid



Foreign Keys

Constraint	Columns	References	Delete/update action
division	divisionid	pears.Division (divisionid)	ON DELETE SET NULL
SMTPServer	SMTPServer	pears.MailServer (MailServerID)	ON DELETE SET NULL
IMAPServer	IMAPServer	pears.MailServer (MailServerID)	ON DELETE SET NULL
IQXNetEmailDetails	IQXNetEmailDetailsID	pears.IQXNetEmailDetails (IQXNetEmailDetailsID)	ON DELETE SET NULL

Referenced By

Table	Constraint	Columns	Referenced columns
pears.Borough	AgencyDetails	AgencyID	agencyid
pears.Country	AgencyDetails	AgencyID	agencyid
pears.County	AgencyDetails	AgencyID	agencyid
pears.globaldocument	AgencyDetails	AgencyID	agencyid
pears.mailmerge	agencydetails	agencyid	agencyid
pears.report	agencydetails	agencyid	agencyid
pears.staff	agencydetails	agencyid	agencyid
pears.TempHoliday	agencydetails	agencyid	agencyid
pears.templatestore	agencydetails	agencyid	agencyid
pears.Town	AgencyDetails	AgencyID	agencyid

Indexes

Name	Type	Columns	Detail
agencydetails_name	Index	name	

Triggers

Name	Timing	Event
WPK_agencydetails_BRANCH	after	insert,delete,update order 1

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."agencydetails"
-- Table comment: Branch details. A branch usually represents a physical
location.
-- Statement count: 9

CREATE TABLE "pears"."agencydetails" (
```



```
"agencyid"          CHAR(20) NOT NULL
,"name"             CHAR(30) NULL
,"defaultreportdirectory" CHAR(100) NULL
,"wpdocdirectory"   CHAR(100) NULL
,"currency"         CHAR(3) NULL
,"AddressEtc1"      long VARCHAR NULL
,"AddressEtc2"      long VARCHAR NULL
,"AddressEtc3"      long VARCHAR NULL
,"AddressEtc4"      long VARCHAR NULL
,"AddressEtc5"      long VARCHAR NULL
,"AddressEtc6"      long VARCHAR NULL
,"Analysis"         CHAR(50) NULL
,"divisionid"       CHAR(20) NULL
,"docstoragefolder" CHAR(100) NULL
,"SMTPServer"       CHAR(20) NULL
,"IMAPServer"       CHAR(20) NULL
,"Extra1"           long VARCHAR NULL
,"Extra2"           long VARCHAR NULL
,"Extra3"           long VARCHAR NULL
,"IQXNetEmailDetailsID" CHAR(20) NULL
,PRIMARY KEY ("agencyid" ASC)
)
GO

COMMENT ON TABLE "pears"."agencydetails" IS
    'Branch details. A branch usually represents a physical location.'
GO

-----
--      Create foreign keys
-----

ALTER TABLE "pears"."agencydetails"
    ADD FOREIGN KEY "division" ("divisionid" ASC)
    REFERENCES "pears"."Division" ("divisionid")
    ON DELETE SET NULL
GO

ALTER TABLE "pears"."agencydetails"
    ADD FOREIGN KEY "SMTPServer" ("SMTPServer" ASC)
    REFERENCES "pears"."MailServer" ("MailServerID")
    ON DELETE SET NULL
GO
```



```
ALTER TABLE "pears"."agencydetails"
  ADD FOREIGN KEY "IMAPServer" ("IMAPServer" ASC)
  REFERENCES "pears"."MailServer" ("MailServerID")
  ON DELETE SET NULL
GO

ALTER TABLE "pears"."agencydetails"
  ADD FOREIGN KEY "IQXNetEmailDetails" ("IQXNetEmailDetailsID" ASC)
  REFERENCES "pears"."IQXNetEmailDetails" ("IQXNetEmailDetailsID")
  ON DELETE SET NULL
GO

CREATE INDEX "agencydetails_name" ON "pears"."agencydetails"
  ( "name" )
GO

CREATE TRIGGER "WPK_agencydetails_BRANCH" after INSERT,DELETE,UPDATE ORDER 1
ON
"pears"."agencydetails"
FOR each statement
BEGIN
  CALL "WPKTrackChange"('P','BRANCH')
END
GO

COMMENT TO PRESERVE FORMAT ON TRIGGER
"pears"."agencydetails"."WPK_agencydetails_BRANCH" IS
{CREATE TRIGGER WPK_agencydetails_BRANCH
  after INSERT,DELETE,UPDATE ORDER 1 ON
agencydetails
FOR each statement
BEGIN
  CALL WPKTrackChange('P','BRANCH')
END
}
GO
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_agencydetails

Last update: 2026/08/07 19:24



