



pears.AvailabilityTemplate



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

User defined availability patterns.

Columns

Column	Type	Null	Default	Comment
AvailTemplateID	char(2)	NOT NULL		
Name	char(50)	NOT NULL		
DivisionID	char(20)	NULL		
TimeFrom	time	NULL		
TimeTo	time	NULL		
PublishToWeb	smallint	NULL	0	

Primary Key

- AvailTemplateID

Foreign Keys

Constraint	Columns	References	Delete/update action
Division	DivisionID	pears.Division (divisionid)	ON DELETE SET NULL

Referenced By

Table	Constraint	Columns	Referenced columns
pears.TempShift	AvailabilityTemplate	AvailTemplateID	AvailTemplateID

Indexes

- No indexes found.



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."AvailabilityTemplate"
-- Table comment: User defined availability patterns.
-- Statement count: 3

CREATE TABLE "pears"."AvailabilityTemplate" (
    "AvailTemplateID"          CHAR(2) NOT NULL
    , "Name"                   CHAR(50) NOT NULL
    , "DivisionID"             CHAR(20) NULL
    , "TimeFrom"               TIME NULL
    , "TimeTo"                 TIME NULL
    , "PublishToWeb"           SMALLINT NULL DEFAULT 0
    , PRIMARY KEY ("AvailTemplateID" ASC)
)
GO

COMMENT ON TABLE "pears"."AvailabilityTemplate" IS
    'User defined availability patterns.'
GO

ALTER TABLE "pears"."AvailabilityTemplate"
    ADD FOREIGN KEY "Division" ("DivisionID" ASC)
    REFERENCES "pears"."Division" ("divisionid")
    ON DELETE SET NULL
GO
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_availabilitytemplate

Last update: **2026/08/07 19:24**

