



pears.BroadbeanChannels



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Broadbean Channels

Columns

Column	Type	Null	Default	Comment
BroadbeanChannelid	char(20)	NOT NULL		
Broadbeanvacancyid	char(20)	NULL		
vacancyid	char(20)	NULL		
ChannelName	char(100)	NULL		
channelid	char(100)	NULL		
FreeToPost	tinyint	NULL		
CostPerPost	char(10)	NULL		
ChannelSummary	char(100)	NULL		
QuotaInformation	char(100)	NULL		
cost	double	NULL		
currency	char(10)	NULL		
postedtime	timestamp	NULL		
removaltime	timestamp	NULL		
adverturl	char(200)	NULL		
slots	char(20)	NULL		
responses	integer	NULL		
views	integer	NULL		
returncode	integer	NULL		
returncodeclass	char(100)	NULL		

Primary Key

- BroadbeanChannelid



Foreign Keys

Constraint	Columns	References	Delete/update action
BroadbeanVacancy	Broadbeanvacancyid	pears.BroadbeanVacancy (Broadbeanvacancyid)	ON DELETE CASCADE
vacancy	vacancyid	pears.vacancy (vacancyid)	ON DELETE CASCADE

Referenced By

Table	Constraint	Columns	Referenced columns
pears.BroadbeanCandidate	BroadbeanChannels	BroadbeanChannelid	BroadbeanChannelid

Indexes

- No indexes found.

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."BroadbeanChannels"
-- Table comment: Broadbean Channels
-- Statement count: 4

CREATE TABLE "pears"."BroadbeanChannels" (
  "BroadbeanChannelid"      CHAR(20) NOT NULL
, "Broadbeanvacancyid"      CHAR(20) NULL
, "vacancyid"               CHAR(20) NULL
, "ChannelName"             CHAR(100) NULL
, "channelid"               CHAR(100) NULL
, "FreeToPost"              tinyint NULL
, "CostPerPost"             CHAR(10) NULL
, "ChannelSummary"          CHAR(100) NULL
, "QuotaInformation"         CHAR(100) NULL
, "cost"                    DOUBLE NULL
, "currency"                CHAR(10) NULL
, "postedtime"              TIMESTAMP NULL
, "removaltime"             TIMESTAMP NULL
, "adverturl"               CHAR(200) NULL
```



```
, "slots" CHAR(20) NULL
, "responses" INTEGER NULL
, "views" INTEGER NULL
, "returncode" INTEGER NULL
, "returncodeclass" CHAR(100) NULL
, PRIMARY KEY ("BroadbeanChannelid" ASC)
)
GO

COMMENT ON TABLE "pears"."BroadbeanChannels" IS
    'Broadbean Channels'
GO

ALTER TABLE "pears"."BroadbeanChannels"
    ADD FOREIGN KEY "BroadbeanVacancy" ("Broadbeanvacancyid" ASC)
    REFERENCES "pears"."BroadbeanVacancy" ("Broadbeanvacancyid")
    ON DELETE CASCADE
GO

ALTER TABLE "pears"."BroadbeanChannels"
    ADD FOREIGN KEY "vacancy" ("vacancyid" ASC)
    REFERENCES "pears"."vacancy" ("vacancyid")
    ON DELETE CASCADE
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_broadbeanchannels

Last update: **2026/08/07 19:24**

