



pears.CardReaderCard



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Current state (in or out) for each swipe card or equivalent.

Columns

Column	Type	Null	Default	Comment
CardReaderCardID	char(20)	NOT NULL		
MachineID	char(20)	NULL		
CardID	char(20)	NULL		
inorout	smallint	NULL		

Primary Key

- CardReaderCardID

Foreign Keys

Constraint	Columns	References	Delete/update action
CardReaderSettings	MachineID	pears.CardReaderSettings (MachineID)	

Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
CardReaderCard_cardid	Index	CardID	



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."CardReaderCard"
-- Table comment: Current state (in or out) for each swipe card or
equivalent.
-- Statement count: 4
```

```
CREATE TABLE "pears"."CardReaderCard" (
  "CardReaderCardID"          CHAR(20) NOT NULL
, "MachineID"                  CHAR(20) NULL
, "CardID"                     CHAR(20) NULL
, "inorout"                    SMALLINT NULL
, PRIMARY KEY ("CardReaderCardID" ASC)
)
GO
```

```
COMMENT ON TABLE "pears"."CardReaderCard" IS
  'Current state (in or out) for each swipe card or equivalent.'
GO
```

```
ALTER TABLE "pears"."CardReaderCard"
  ADD FOREIGN KEY "CardReaderSettings" ("MachineID" ASC)
  REFERENCES "pears"."CardReaderSettings" ("MachineID")
GO
```

```
CREATE INDEX "CardReaderCard_cardid" ON "pears"."CardReaderCard"
  ( "CardID" )
GO
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_cardreadercard

Last update: 2026/08/07 19:24



