



pears.CardReaderImport



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Import table for Time & Attendance data (eg card swipes etc).

Columns

Column	Type	Null	Default	Comment
ID	char(20)	NOT NULL		
BearBoxID	integer	NULL		
MachineID	char(20)	NULL		
CardID	char(20)	NULL		
location	char(100)	NULL		
thetime	timestamp	NULL		
whenentered	timestamp	NULL		
processed	smallint	NULL		
personid	char(20)	NULL		
cardholder	char(100)	NULL		
clockin	smallint	NULL		
event	char(20)	NULL		
misread	smallint	NULL		

Primary Key

- ID

Foreign Keys

Constraint	Columns	References	Delete/update action
CardReaderSettings	MachineID	pears.CardReaderSettings (MachineID)	



Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
CardReaderImport_personid	Index	personid	
CardReaderImport_cardid	Index	CardID	

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."CardReaderImport"
-- Table comment: Import table for Time & Attendance data (eg card swipes
etc).
-- Statement count: 5
```

```
CREATE TABLE "pears"."CardReaderImport" (
    "ID" CHAR(20) NOT NULL
    , "BearBoxID" INTEGER NULL
    , "MachineID" CHAR(20) NULL
    , "CardID" CHAR(20) NULL
    , "location" CHAR(100) NULL
    , "thetime" TIMESTAMP NULL
    , "whenentered" TIMESTAMP NULL
    , "processed" SMALLINT NULL
    , "personid" CHAR(20) NULL
    , "cardholder" CHAR(100) NULL
    , "clockin" SMALLINT NULL
    , "event" CHAR(20) NULL
    , "misread" SMALLINT NULL
    , PRIMARY KEY ("ID" ASC)
)
GO
```

```
COMMENT ON TABLE "pears"."CardReaderImport" IS
```



```
'Import table for Time & Attendance data (eg card swipes etc).'
```

```
GO
```

```
ALTER TABLE "pears"."CardReaderImport"
```

```
  ADD FOREIGN KEY "CardReaderSettings" ("MachineID" ASC)
```

```
  REFERENCES "pears"."CardReaderSettings" ("MachineID")
```

```
GO
```

```
CREATE INDEX "CardReaderImport_personid" ON "pears"."CardReaderImport"
```

```
  ( "personid" )
```

```
GO
```

```
CREATE INDEX "CardReaderImport_cardid" ON "pears"."CardReaderImport"
```

```
  ( "CardID" )
```

```
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_cardreaderimport

Last update: **2026/08/07 19:24**

